PROFROID

Proven Solutions.

Cooling | Heating

Sustainable. Efficient.

QuietCO$_2$OL

CO_2 transcritical refrigeration concept for small stores and extensions

New:
- **Larger receiver available**
- **Online CO_2 and oil charge estimation tool**

- PFAS/TFA free refrigerant
- Silent
- Compact, low refrigerant charge, easy service
- **Up to 70m pipe length: MCHX gas cooler, 2 receiver sizes per model**
- Inverter on compressor, EC fans
- Suction filter, Electrical protection for consumers
- 80 bar stand still pressure
- Simple / intuitive display
- Connect to BMS via modbus RS485

Brochures available here:

LRQA CERTIFIED ISO 9001

1–10 kW MT cooling capacity

1–7 kW LT cooling capacity

QuietCO2OL

CO_2 and oil charge estimation tool:

The QuietCO2OL range is split into 7 sizes and 14 models to best suit your needs.

MT models	Q_0 (kW) Min	Q_0 (kW) Max	Noise level dB(A) @10m	Fan #	Voltage (V/Ph/Hz)	Imax (A)	Cooler protections type	Cooler protections qty	Ø Suct	Ø Liq	Receiver volume (l)	Dimensions L×W×H (mm)	Weight (kg)
QC MT30 ACO 4 AC MX	0,8	3,2	29	1	230/1/50 +N+G	13,4	10A 230/1/50 +N	2	3/8"	3/8"	2 x 2,2 cat I	1200 x 390 x 1058	112
QC MT30 ACO 6 AC MX *											3 x 2,2 cat I		116
QC MT30 ACO 4 EC MX	0,8	3,2	29	1	230/1/50 +N+G	14,0	10A 230/1/50 +N	2			2 x 2,2 cat I		117
QC MT30 ACO 6 EC MX *											3 x 2,2 cat I		121
QC MT45 ACO 4 EC MX	1,1	4,5	31	1	230/1/50 +N+G	19,7	10A 230/1/50 +N	2			2 x 2,2 cat I		117
QC MT45 ACO 6 EC MX *											3 x 2,2 cat I		121
QC MT67 ACO 6 EC MX	1,8	7,2	34	1	400/3/50 +N+G	28,2	10A 230/1/50 +N	3			3 x 2,2 cat I		125
QC MT67 ACO 12 EC MX *											12,5 cat II	1200 x 534 x 1196	153
QC MT100 ACO 6 EC MX	2,4	9,7	35	2	400/3/50 +N+ G	19,5	10A 230/1/50 +N	3			3 x 2,2 cat I	1200 x 390 x 1464	157
QC MT100 ACO 12 EC MX *											12,5 cat II	1200 x 534 x 1464	178

LT models	Q_0 (kW) Min	Q_0 (kW) Max	Noise level dB(A) @10m	Fan #	Voltage (V/Ph/Hz)	Imax (A)	Cooler protections type	Cooler protections qty	Ø Suct	Ø Liq	Receiver volume (l)	Dimensions L×W×H (mm)	Weight (kg)
QC LT75 ACO 4 EC MX	1,3	2,9	32	1	230/1/50 +N+G	19,1		0	3/8"	3/8"	2 x 2,2 cat I	1200 x 690 x 1058	165
QC LT75 ACO 6 EC MX *											3 x 2,2 cat I		169
QC LT112 ACO 6 EC MX	2,0	4,6	35	1	400/3/50 +N+ G	17,5	10A 400/3/50 +N	1	1/2"	3/8"	3 x 2,2 cat I	1200 x 690 x 1668	210
QC LT112 ACO 12 EC MX											12,5 cat II	1200 x 774 x 1668	233
QC LT167 ACO 6 EC MX	2,9	6,5	37	2	400/3/50 +N+ G	31,4	20A 400/3/50 +N	1			3 x 2,2 cat I	1200 x 690 x 1668	220
QC LT167 ACO 12 EC MX											12,5 cat II	1200 x 774 x 1668	243

*Evaporating temp -8°C MT & - 32°C LT @ ambient 32°C; * Available February 2025*

Options: Coil corrosion protection, Water cooled versions

Proven Solutions. Cooling | Heating Sustainable. Efficient.

Ref. no. Profroid_QuietCO2OL_eu_leaflet_EN_170924, All trademarks are the property of their respective owners, ©2024 Profroid. All Rights Reserved.

PROFROID

Profroid reserves the right to change certain information and specifications contained in this document at any time and without prior notice. Since standards, specifications and designs are subject to occasional change, please ask for confirmation of the information given in this publication

www.profroid.com