



Licensed by Carrier Corporation

Areor[®] Stepped G

Plug-in counter island with minimized energy consumption and maximized transparency



Benefits at a glance

- Quick return of investment thanks to outstanding energy efficiency, labelled A
- Highly transparent design for a modern and optimal product presentation
- Plug & play connectivity options to various store gateways
- 3M1 temperature class for a wide range of product applications



Areor® Stepped G

Plug-in counter island with minimized energy consumption and maximized transparency

Standard configuration

- Highly transparent stepped plug-in counter-island for promotional sales
- Stepped superstructure with acrylic sidewalls and one (Areor® SD) or two (Areor® ST) adjustable glass shelves
- Bottom shelf and plinth of galvanized steel with powder-coated finish, sidewalls and front air deflectors of PVC, outside and inside color black (RAL 9005)
- Stainless steel bumper (Areor® ST 1052 G)
- Energy optimized fans
- Electronic controller
- Digital thermometer (solar)
- Factory installed castors
- Sliding condensing unit
- Natural refrigerant R290 (propane)

Customization

- Connectivity options to various store gateways
- LED lighting for canopy and shelves, light color Neutral White 4000K, Cool White 5700K, Fresh red
- Price rails, 40 and 60 mm
- Large selection of CCR-certified powder coating colors internally and externally
- Wooden cladding
- Multiplex kit back-to-back
- Stainless steel bumper (Areor® SD/ST 1253 G)
- Transparent product dividers and presenter, V or Z shaped
- Cabinet feet
- Remote CO₂ version (on request)



Areor® SD 1253 G




Areor® ST 1253 G




Areor® ST 1052 G

Available in:

Air COOL




Areor® SD 1253 G
(Side view)




Areor® SD 1253 G
(Front view)

Air COOL




Areor® ST 1253 G
(Side view)




Areor® ST 1253 G
(Front view)

Air COOL



Areor® ST 1052 G
(Side view)



Areor® ST 1052 G
(Front view)

Areor® Stepped ²	Unit	SD 1253 G	ST 1253 G	ST 1052 G
Temperature	[°C]	-1...+1	-1...+1	-1...+1
Refrigerant		R290	R290	R290
Width (without / with bumper)	[mm]	1290 / 1410	1290 / 1410	- / 1020
Depth (without / with bumper)	[mm]	1080 / 1150	1080 / 1150	- / 1045
Height	[mm]	1150	1280	1240
Volume	[l]	205	254	21
Total display area	[m ²]	2,02	2,66	2,0
Energy consumption**	[kWh/d]	2,37	3,53	3,4
Average heat dissipation	[W]	99	147	145
Temperature class*		M1	M1	M1

* At climate class 3 according to ISO 23953 | ** Measured in accordance with the applicable EU delegated regulation

1 Energy Labels might change depending on cabinet configuration and are based on R290 plug-in refrigerant technology

2 All technical data includes LED lighting consumption where applicable



Licensed by Carrier Corporation

CCR reserves the right to change certain information and specifications contained in this document at any time and without prior notice. Since standards, specifications and designs are subject to occasional change, please ask for confirmation of the information given in this publication.

www.ccr.com

